Swing Check Valve

Sizes 2" thru 30" / 50mm thru 750mm



Written Specifications:

CHECK VALVE SHALL BE OF SWING TYPE AND SHALL MEET THE MATERIAL REQUIREMENTS OF AWWA SPECIFICATION C508. THE VALVE SHALL CONTAIN THE FOLLOWING: IRON BODY (PRIMER COATED)

SINGLE BRONZE MOUNTED GATE FOR NON-SHOCK

WORKING PRESSURE OF 175 PSI FOR 2" THRU 12" SIZES AND 150 PSI FOR 14" THRU 30" SIZES

HYDROSTATIC TESTING OF DOUBLE THE WORKING PRESSURE

FOR ALL SIZES

THE SEAT RING (SEAL RING) SHALL BE BRONZE OR STAINLESS STEEL; THE GATE RING (DISC RING) SHALL BE BRONZE OR RUBBER AND THE ENDS SHALL BE FLANGED ÀNSI CLASS 125#

THE VALVE SHALL BE CONSTRUCTED SO THAT BY SIMPLY UNBOLTING AND LIFTING OFF THE COVER, THE INTERNAL WORKING PARTS MAY EASILY BE REMOVED AND REPLACED WITHOUT REMOVING THE VALVE FROM THE LINE. THE VALVE SHALL BE FURNISHED WITH AN OUTSIDE LEVER AND SPRING.

THE VALVE SHALL PERMIT FLOW IN ONE DIRECTION ONLY; BE TIGHT SEATING WHEN THE OUTLET PRESSURE EXCEEDS THE INLET PRESSURE AND BE SUITABLE FOR MOUNTING IN HORIZONTAL OR VERTICAL LINES.

THE VALVE SHALL HAVE A STAINLESS STEEL SHAFT (HINGE PIN) SUPPORTED BY BRONZE BEARINGS AND SEALED BY AN ADJUSTABLE PACKING GLAND WITH A COMPRESSION TYPE PACKING.

THE VALVE SHALL BE EQUAL IN ALL RESPECTS TO THE MODEL 90LS AS MANUFACTURED BY THE FLOMATIC CORPORATION.

Swing Check Valve Ordering Information

Quantity:

Size: 2" thru 30" / 50mm thru 750mm

Type: 90LS or 92LS

Connection Type: Flange 125# Gate Ring: Bronze or Buna-n

Flomatic Corporation can accept no responsibility for possible errors in catalogues, brochures and other printed material. Flomatic Corporation reserves the right to alter its products without notices. This also applies to product already agreed. All trademarks in this material are property of the respective companies. All right reserved. ©2011 Flomatic Corporation. The drawings & information on this drawing sheet are the sole & exclusive property of Flomatic Corporation. Any reproduction, distribution, display or use of these drawingsor information in whole or in part without written authorization of Flomatic Corporation is strictly prohibited.



FLOMATIC CORPORATION GLENS FALLS, N.Y. 12801 PHONE (518) 761-9797 FAX (518) 761-9798