



DANFOSS FLOMATIC

**Cycle Gard® Max flow - spring rating**

Model	Max GPM	Min GPM	spring range
1/2" Cycle Gard I	18	1	15-75/150
3/4" Cycle Gard I	18	1	15-75/150
1" Cycle Gard I	30	1	15-75/150
1" Cycle Gard IV	30	1	15-75/150
1-1/4" Cycle Gard I	30	1	15-75/150
1-1/4" Cycle Gard I Hy-Flow	70	1	15-75/150
1-1/2" Cycle Gard I	70	1	15-75/150
2" Cycle Gard I	70	1	15-75/150
1" Hydrostat	25	1	35-65
1-1/2" Cyclegard CI	70	1	25-175
2" Cyclegard CI	110	1	25-175
3" Flanged CI	240	1	25-175
4" Cyclegard CI	440	1	25-175
6" Cyclegard CI	1000	1	25-175
8" Cyclegard CI	1800	1	25-175
1-1/4" & 1-1/2" Cycle Gard II	70	1	25-175/30-300
2" Cycle Gard II	110	1	25-175/30-300
2-1/2" Cycle Gard II	160	1	25-175/30-300
3" Cycle Gard II	240	1	25-175/30-300
4" Cycle Gard II	440	1	25-175/30-300
6" Cycle Gard II	1000	1	25-175/30-300
8" Cycle Gard II	1800	1	25-175/30-300
10" Cycle Gard II	2600	1	25-175/30-300

12" Cycle Gard II	4000	1	25-175/30-300
-------------------	------	---	---------------

!!!!Flow rates based on 10ft/sec!!!!