

# Butterfly Valve

Sylax®3



## Bare Stem Torque Values



SIZE		145 PSI / 10 BAR			232 PSI / 16 BAR		
INCH	MM	lbf·in	lbf·ft	Nm	lbf·in	lbf·ft	Nm
2	50	150	13	17	177	15	20
2.5	65	168	14	19	221	18	25
3	80	239	20	27	274	23	31
4	100	398	33	45	451	38	51
5	125	566	47	64	673	56	76
6	150	850	71	96	1151	96	130
8	200	1726	144	195	2036	170	230
10	250	3151	263	356	3496	291	395
12	300	4301	358	486	4868	406	550

Torque:

$$1\text{N}\cdot\text{m} = 8.8507 \text{ lbf}\cdot\text{in}$$

$$1\text{N}\cdot\text{m} = 0.7376 \text{ lbf}\cdot\text{ft}$$

Flomatic Corporation can accept no responsibility for possible errors in catalogues, brochures and other printed material. Flomatic Corporation reserves the right to alter its products without notices. This also applies to product already agreed. All trademarks in this material are property of the respective companies. All right reserved. ©2019Flomatic Corporation. The drawings & information on this drawing sheet are the sole & exclusive property of Flomatic Corporation. Any reproduction, distribution, display or use of these drawings or information in whole or in part without written authorization of Flomatic Corporation is strictly prohibited.  
www.flomatic.com



16-Feb-18  
SS3TORQUE Rev A (2/19)

Flomatic Corporation  
Glens Falls, NY 12801  
Phone (518) 761-9797  
Fax (518) 761-9798