

Model 45 Azure® Butterfly Valve
Bare Stem Torque Values

SIZE		Pressure Difference	AWWA C504 Class 150 B		
INCH	MM		lbf in	lbf ft	Nm
3	80	0 psi	177	15	20
		150 psi	239	20	27
4	100	0 psi	363	30	41
		150 psi	363	30	41
6	150	0 psi	717	60	81
		150 psi	1018	85	115
8	200	0 psi	1496	125	169
		150 psi	1921	160	217
10	250	0 psi	2222	185	251
		150 psi	3540	295	400
12	300	0 psi	5098	425	576
		150 psi	5399	450	610
14	350	0 psi	8098	675	915
		150 psi	8514	710	962
16	400	0 psi	10789	899	1219
		150 psi	12595	1050	1423
18	450	0 psi	13188	1099	1490
		150 psi	18710	1559	2114
20	500	0 psi	17392	1449	1965
		150 psi	23861	1989	2696
24	600	0 psi	31181	2599	3523
		150 psi	37536	3128	4241

Torque:
1Nm = 8.8507 lbf in
1Nm = 0.7376 lbf ft

Flomatic Corporation can accept no responsibility for possible errors in catalogues, brochures and other printed material. Flomatic Corporation reserves the right to alter its products without notices. This also applies to product already agreed. All trademarks in this material are property of the respective companies. All rights reserved. ©2019Flomatic Corporation. The drawings & information on this drawing sheet are the sole & exclusive property of Flomatic Corporation. Any reproduction, distribution, display or use of these drawings or information in whole or in part without written authorization of Flomatic Corporation is strictly prohibited. www.flomatic.com