Break-Off Plug

Submersible Pump Valves FLAM

Sizes 2-3/8" thru 9-5/8"/ 60 mm thru 245 mm

FLOMATIC[®] Flomatic Corporation

Instructions:


- A. Drop a length of pipe (see chart) down the riser pipe.
- B. The break-off plug breaks allowing the riser pipe to drain.


Benefits:


- A. Reduces the lifting weight. By 25% to 50%
- B. Eliminates water splashing at the surface.
- C. Simply replace the Break-Off Plug for re-installation. WARNING: Break-Off Plug MUST be installed with teflon tape.

Features:

- A. No corrosive parts (304 Stainless Steel)
- B. Available in all submersible pump check valves (80 Deep Well series) from 2-3/8" thru 9-5/8".







Valve Size		Part#	NPT	A		В		Break-Off Pipe			
								Size		Length	
inch	mm	304 Stainless Steel	Size	inch	mm	inch	mm	inch	mm	feet	meters
2-3/8	60	76098-2DW	3/8	1-3/4	45	5/16	8	1-1/2	40	10	3
2-7/8	73	76098-2DW	3/8	1-3/4	45	5/16	8	1-1/2	40	10	3
3-1/2	89	76098-3	3/8	2-1/2	64	5/16	8	1-1/2	40	10	3
4-1/2	114	76098-5DW	3/4	2-1/2	64	5/8	16	2-1/2	65	10	3
5	127	76098-5DW	3/4	2-1/2	64	5/8	16	2-1/2	65	10	3
5-1/2	140	76098-7DW	3/4	3	76	5/8	16	4	100	4	1.2
6-5/8	168	76098-7DW	3/4	3	76	5/8	16	4	100	4	1.2
7	178	76098-7DW	3/4	3-1/2	89	5/8	16	4	100	4	1.2
7-5/8	194	76098-7DW	3/4	3-1/2	89	5/8	16	4	100	4	1.2
8-5/8	219	76098-9DW	3/4	4-1/2	114	5/8	16	5	125	4	1.2
9-5/8	245	76098-9DW	3/4	5	127	5/8	16	5	125	4	1.2

Flomatic Corporation can accept no responsibility for possible errors in catalogues, brochures and other printed material. Flomatic Corporation reserves the right to alter its products without notices. This also applies to product already agreed. All trademarks in this material are property of the respective companies. All right reserved. ©2016 Flomatic Corporation. The drawings & information on this drawing sheet are the sole & exclusive property of Flomatic Corporation. Any reproduction, distribution, display or use of these drawings or information in whole or in part without written authorization of Flomatic Corporation is strictly prohibited.

