



API Specification 5B Table 6 (Short Casing) and Table 7 (Long Casing) Threads – Designed for J55

How to Order Short / Long Casing Deep Well Valves

If you don't know the Weight – then choose by male thread length

Valve Size	Weight Thread and Coupling	Body Style Threads	Thread Option	Break-off Plug
7939 = 4-1/2" 7940 = 5" 4088 = 5-1/2" 4089 = 6-5/8" 4090 = 7" 4091 = 7-5/8" 4092 = 8-5/8" 4093 = 9-5/8"	n/a = 4-1/2" 9.5# (POA) 1 = 4-1/2" other (Standard) n/a = 5" 11.5# (POA) 2 = 5" other (Standard) n/a = 5-1/2" (Standard) n/a = 6-5/8" (Standard) n/a = 7" 17# (Standard) 3 = 7" other (POA) n/a = 7-5/8" (Standard) n/a = 8-5/8" 24# (Standard) 4 = 8-5/8" other (POA) n/a = 9-5/8" (Standard)	MDW = male inlet x female outlet threads (Standard) DW = female inlet x female outlet (POA)	8SL = 8 round short casing inlet and long casing outlet (Standard) 8S = 8 round Short Casing inlet & outlet (POA) 8L = 8 round Long Casing inlet & outlet (POA)	PLG = comes standard with break-off plug N/A = no plug (POA)

Valve Size	Weight Thread & Coupling	Body Style Threads	Thread Option	Break-Off Plug
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

4-1/2" 9.5# - MALE THREAD LENGTH 2.000"
 4-1/2" other – MALE THREAD LENGTH 2.625"
 5" 11.5# - MALE THREAD LENGTH 2.500"
 5" other – MALE THREAD LENGTH 2.750"
 5-1/2" (all) – MALE THREAD LENGTH 2.875"
 6-5/8" (all) – MALE THREAD LENGTH 3.125"
 7" 17# - MALE THREAD LENGTH 2.375"
 7" other – MALE THREAD LENGTH 3.125"
 7-5/8" (all) – MALE THREAD LENGTH 3.250"
 8-5/8" 24# - MALE THREAD LENGTH 3.000"
 8-5/8" other – MALE THREAD LENGTH 3.750"
 9-5/8" (all) – MALE THREAD LENGTH 3.375

API Specification 5B Table 13 External-Upset Tubing Threads How to Order External-Upset Tubing (EU) Deep Well Valves

Valve Size	Body Style Thread	Thread Option	Break-off Plug
7937 = 2-3/8" 7936 = 2-7/8" 7938 = 3-1/2" 7939 = 4-1/2"	MDW = male inlet x female outlet threads (STANDARD)	8EU = 8 round External Upset Tubing Threads (STANDARD)	PLG = comes standard with break-off plug N/A = no plug (POA)

Valve Size

Body Style Threads

Thread Option

Break-Off Plug