Enviro Check®

Model 100DPE

Size 1" x 1-1/4" / 25 mm x 32 mm

FLOMATIC®
Flomatic Corporation

LEAD FREE
NSF/ANSI 61

Materials









Max Temp 180°F (82°C)
Max Pressure 400psi (28bar)

Item #	Qty	Description	Material	ASTM
1	1	Body	Unleaded Bronze	C89833
2	1	Screw	Stainless Steel	302
3	1	Dome	Delrin®	500P
4	1	Disc	Buna-N	N-5007
5	1	Spring	Stainless Steel	302
6	1	Guide	Colcon®	M90

Dimensions (MNPT X FNPT both ends)

Patent #'s 4,971,093 & 6,581,633

ANSI B1.20.1

Size		Part #	A		B		ID FNPT	OD MNPT	Weight	
inch	mm		inch	mm	inch	mm			lbs	kg
1	25	4231E	1.91	49	3.65	93	1" NPT	1-1/4" NPT	1.2	.54

Flomatic Corporation can accept no responsibility for possible errors in catalogues, brochures and other printed material. Flomatic Corporation reserves the right to alter its products without notices. This also applies to product already agreed. All trademarks in this material are property of the respective companies. All rights reserved. ©2026 Flomatic Corporation. The drawings & information on this drawing sheet are the sole & exclusive property of Flomatic Corporation. Any reproduction, distribution, display or use of these drawings or information in whole or in part without written authorization of Flomatic Corporation is strictly prohibited. www.flomatic.com

FLOMATIC® VALVES

November 5, 1997
Dwg No: S4231-2E Rev: J (2/26)

FLOMATIC CORPORATION
GLENS FALLS, N.Y. 12801
PHONE (518) 761-9797
FAX (518) 761-9798