

**Written Specifications:**

The Enviro Check® valve shall incorporate a stemless type spring loaded, closing system. This system is normally in the closed position and capable of opening automatically under normal flow conditions. Under stoppage of flow, the valve shall be capable of preventing backflow by an elastomer seal, which is leak tight. In addition, the valve shall have a self-cleaning seat and non-rotating closing system.

The valve is to be maintenance free. All components shall be non-corrosive materials of sturdy construction capable of withstanding repeated normal operation without failure of excessive wear.

1/2" thru 2-1/2" valve may be installed vertically or horizontally. For sizes larger than 2-1/2" please consult factory or refer to 80DIX or 80DI VFD valves.

The valve shall be equal in all respects to all Models 80E's and 100E's as manufactured by Flomatic Corporation.

**Enviro Check® Valve Ordering Information**

Quantity:

Size: Available 1/4" thru 4"

Flomatic Corporation can accept no responsibility for possible errors in catalogues, brochures and other printed material. Flomatic Corporation reserves the right to alter its products without notices. This also applies to product already agreed. All trademarks in this material are property of the respective companies. All right reserved. ©2011 Flomatic Corporation. The drawings & information on this drawing sheet are the sole & exclusive property of Flomatic Corporation. Any reproduction, distribution, display or use of these drawings or information in whole or in part without written authorization of Flomatic Corporation is strictly prohibited.