Enviro Check®

Model 80BE

Sizes 1-1/2" / 40 mm
Double Tap

Flomatic Corporation

LEAD FREE
NSF/ANSI 61

Materials



Max Temp 180°F (82°C)
Max Pressure 400psi (28bar)

Item #	Qty	Description	Material	ASTM
1	1	Body	Unleaded Bronze	C89833
2	1	Screw	Stainless Steel	302
3	1	Dome	Celcon®	M90
4	1	Disc	Buna-N	N5007
5	1	Spring	Stainless Steel	302
6	1	Guide	Celcon®	M90

Dimensions (FNPT X FNPT)

Patent #'s 4,971,093 & 6,581,633

ANSI B1.20.1

Size		Part #	ØA		B		C		D		E	F	Weight	
inch	mm		inch	mm	inch	mm	inch	mm	inch	mm	(Inlet NPT)	(Outlet NPT)	lbs	kg
1-1/2	40	4053E	2.60	66	4.63	118	1.03	26	1.13	29	1/8	1/4	2.75	1.25
1-1/2	40	7973E	2.60	66	4.63	118	1.03	26	1.13	29	1/4	1/4	2.75	1.25
1-1/2	40	8987E	2.60	66	4.63	118	1.03	26	1.13	29	1/4	1/8	2.75	1.25
1-1/2	40	7953E	2.60	66	4.63	118	1.03	26	1.13	29	1/8	1/8	2.75	1.25

Flomatic Corporation can accept no responsibility for possible errors in catalogues, brochures and other printed material. Flomatic Corporation reserves the right to alter its products without notices. This also applies to product already agreed. All trademarks in this material are property of the respective companies. All rights reserved. ©2024 Flomatic Corporation. The drawings & information on this drawing sheet are the sole & exclusive property of Flomatic Corporation. Any reproduction, distribution, display or use of these drawingsor information in whole or in part without written authorization of Flomatic Corporation is strictly prohibited. www.flomatic.com

FLOMATIC® VALVES

January 12, 1998
Dwg No: S4053E Rev: J (9/24)

FLOMATIC CORPORATION
GLENS FALLS, N.Y. 12801
PHONE (518) 761-9797
FAX (518) 761-9798