

Silent Check Valve

Model 402/402R

FLOMATIC[®]

Sizes 2" Thru 24" / 50 mm Thru 600 mm

Flomatic Corporation



Written Specifications:

Globe style silent check valves shall be of silent operating type which reduce or eliminate water hammer shock.

The valve design shall incorporate a center guided, spring loaded poppet, guided at opposite ends and having a short linear stroke that generates a flow area equal to that of the pipe size.

The valve shall operate equally well in the vertical or horizontal position with the flow up or down.

All component parts shall be field replaceable and without the need of special tools. A replaceable guide bushing shall be provided and held in position by the valves spring.

The valve disc shall be convex in sizes up to 6" and concave in 8" and larger to the flow direction providing for disc stabilization, maximum strength and a minimal flow velocity to open the valve.

When specified, a rubber seal shall be furnished to provide zero leakage. The rubber seal shall be glued or chemically adhered.

The valve shall be equal in all respects to the Models 402BT,ST,S6 402BTR,STR,S6R as manufactured by the Flomatic Corporation.

Silent Check Valve Ordering Information

Quantity:

Type: 402BT,ST,S6 or 402BTR,STR,S6R

Size: Available 2" thru 24" (402BTR,STR & S6R 2" thru 12")

End Type: Flanged (ANSI class 125# or 250#)

Seat Ring: Bronze or Stainless Steel (metal-to-metal) or Rubber*

*EPDM SEAL
2"-12" NSF APPROVED
Patent # 6,024,121

Flomatic Corporation can accept no responsibility for possible errors in catalogues, brochures and other printed material. Flomatic Corporation reserves the right to alter its products without notices. This also applies to product already agreed. All trademarks in this material are property of the respective companies. All right reserved. ©2011 Flomatic Corporation. The drawings & information on this drawing sheet are the sole & exclusive property of Flomatic Corporation. Any reproduction, distribution, display or use of these drawings or information in whole or in part without written authorization of Flomatic Corporation is strictly prohibited.

FLOMATIC[®] VALVES

June 25, 2004
Dwg No:S402RS Rev E (7/15)

FLOMATIC CORPORATION
GLENS FALLS, N.Y. 12801
PHONE (518) 761-9797
FAX (518) 761-9798