Swing Check Valve



Sizes 2" Thru 12" / 50 mm & 300 mm Part Data Only

Materials

Max Temp 180°F (82°C) Max Pressure 200psi (14bar)

Item #	Qty	Description	Material	Item #	Qty	Description	Material
1A w/	2	Side Plug w/ O'Ring	Bronze	13A	1	Disc Nut 2 w/resilient disc (2" -3")	Stainless Steel 18-8
1B	1	(for LW/LS)		14AA	1	Disc Ring (4"-12")**	Bronze
2A	A/R	Cover Bolts	Stainless Steel 18-8	15A	1	Seat Ring	Bronze
3A	1	O'Ring	Syn Rubber	16A	1	Spring	Steel
4A	1	Cover	Cast Iron A-126	17A	1	Extended Hinge Pin for LW/LS	Stainless Steel A-276
5A	1	Body	Cast Iron A-126	18A	2	Key for LW/LS	Stainless Steel A-276
6A	1	Hinge Pin	Stainless Steel A-276	19A	1	Set Screw	Steel
7AA	1	Hinge	Bronze (2"-8") Ductile Iron A-536 (10"-12")	20AA	1	Lever Arm for LS	Steel
7AB	1	Hinge w/ keyway (for LW/LS)	Bronze (2"-8") Ductile Iron A-536 (10"-12")	20AB	1	Lever Arm for LW	Steel
8AA	1	Disc Bolt (8" - 12")***	Bronze (10"-12") SS (8")	21A	1	Bracket	Steel
8AB	1	Disc Bolt (8" - 12")***	Bronze (10"-12") SS(8")	22A	2	Hex Head Bracket Bolt	Steel
9AA	2	Disc Bolt O'Ring	Syn Rubber	23A	1	Eye Bolt w/ 2 Hex Nuts	Steel
9AB	2	Disc Bolt Gasket	Syn Rubber	24A	1	Stuffing Box	Bronze
10A	1	Disc Holder	Bronze (2"-8") Cast Iron A-126 (10"-12")	25A	-	Packing	Graphite Filled
11A	1	Disc Plate	Bronze	26A	1	Gland	Bronze
12AA	1	Disc	Nitrile Rubber	27A	1	Weight	Cast Iron A-126
12AB	1	Disc**	Bronze (2"-8") Cast Iron A-126 (10"-12")	28A	1	Set Screw	Steel

^{**} Denotes that part is available only as part of an assembly

MANUFACTURED IN COMPLIANCE WITH AWWA C508 STANDARD

Flomatic Corporation can accept no responsibility for possible errors in catalogues, brochures and other printed material. Flomatic Corporation reserves the right to alter its products without notices. This also applies to product already agreed. All trademarks in this material are property of the respective companies. All right reserved. ©2011 Flomatic Corporation. The drawings & information on this drawing sheet are the sole & exclusive property of Flomatic Corporation. Any reproduction, distribution, display or use of these drawingsor information in whole or in part without written authorization of Flomatic Corporation is strictly prohibited.



^{***}Cast integral (2"-6")