Swing Check Valve



Sizes 14" thru 30" / 350mm thru 750mm Part Data Only

Materials

Max Temp 180°F (82°C) Max Pressure 150psi (10bar)

item #	Qty	Description	Item #	Qty	Description			
1	1	Body	13	***	Ring Clamp			
2	1	Cover	14	1	Ring Clamp Capscrew			
3	1	Body Ring	15	1	Weight Lever Arm			
4	1	Clapper	16	1	Weight			
5 & 8	1	Clapper Arm with Hinge Pin Lever	17	1	Spring Lever Arm			
6	*	Cap Plate Capscrew L/ Washer	18	1	Spring			
7	*	Cap Plate Capscrew	19	1	Spring Bracket			
9	2	Gland	20	1	Spring Eyebolt			
9	2	Bronze Bushing	21	1	Cap Plate			
10	**	Cover Bolts	22	****	Spring Bracket Capscrew			
10	**	Cover Nuts	23	1	Lock Wire			
11	1	Cover Gasket		****	Packing			
12	1	Clapper Ring (Rubber)		1	Calpper Assem w/ Hinge Pin			
Note #1-Items 6, 7, 14, 21 & 23 Not Required			14"	16	" 18"	20"	24"	30"
* # Required			0	3	4	4	4	4
** # Required			16	20	20	20	28	32
*** # Required			0	4	6	6	8	12
**** # Required			2	2	2	2	4	4
***** # Required			4.5	7	7	7	9.5	9.5

MANUFACTURED IN COMPLIANCE WITH AWWA C508 STANDARD

Flomatic Corporation can accept no responsibility for possible errors in catalogues, brochures and other printed material. Flomatic Corporation reserves the right to alter its products without notices. This also applies to product already agreed. All trademarks in this material are property of the respective companies. All right reserved. ©2011 Flomatic Corporation. The drawings & information on this drawing sheet are the sole & exclusive property of Flomatic Corporation. Any reproduction, distribution, display or use of these drawingsor information in whole or in part without written authorization of Flomatic Corporation is strictly prohibited.

