Swing Check Valve



Sizes 14" thru 30" / 350mm thru 750mm Part Data Only

Materials

Max Temp 180°F (82°C) Max Pressure 150psi (10bar)

Item #	Qty	Description	item #	Qt	ty	Description				
1	1	Body	14	1		Ring Clamp Capscrew				
2	1	Cover	15	1		Lever Arm				
3	1	Body Ring	15A	1		Lever Arm Bolt				
4	1	Clapper	15B	1		Weight				
5 & 8	1	Clapper Arm with Hinge Pin Lever	15C	1		Weight Bolt				
6	*	Cap Plate Capscrew L/ Washer	17	1		Cylinder Bracket				
7	*	Cap Plate Capscrew	17A	2	2	Cylinder Bolts				
9	2	Gland	17B	2	2	Cylinder Lock Washers				
9	2	Bronze Bushing	17C	1		Mounting Plate				
10	**	Cover Bolts	17D, E, F	4 E	ach	Mounting Plate Nut, Bolt & Washer				
10	**	Cover Nuts	17G	1		Cylinder				
11	1	Cover Gasket	17H	1		Bushing				
12	1	Clapper Ring (Rubber)	171	1		Flow Control				
13	***	Ring Clamp	17J	1		Rod Cle	Clevis Assembly			
Note #1-Items 6, 7, 14, 21 & 23 Not Required				14"	16"	18"	20"	24"	30"	
* # Required					0	3	4	4	4	4
** # Required					16	20	20	20	28	32
*** # Required					0	4	6	6	8	12

MANUFACTURED IN COMPLIANCE WITH AWWA C508 STANDARD

Flomatic Corporation can accept no responsibility for possible errors in catalogues, brochures and other printed material. Flomatic Corporation reserves the right to alter its products without notices. This also applies to product already agreed. All trademarks in this material are property of the respective companies. All right reserved. ©2011 Flomatic Corporation. The drawings & information on this drawing sheet are the sole & exclusive property of Flomatic Corporation. Any reproduction, distribution, display or use of these drawingsor information in whole or in part without written authorization of Flomatic Corporation is strictly prohibited.

