

Foot Valve

Model 302BT 
Flomatic Corporation

Sizes 2" Thru 24" / 50 mm Thru 600 mm



Written Specifications:

Foot valves shall be cast iron globe style body with integral flanges (ANSI 125#), capable of high flow rates, with minimal headloss.

The poppet assembly shall open automatically under flow and close when flow ceases, providing a positive resilient (EPDM) seal against back pressure or backflow.

The poppet and seat shall be bronze, with the EPDM Seal.

The strainer basket shall be of heavy gauge stainless steel and bolted to the foot valve body. The strainer basket assembly shall have an open area ratio of 3 to 1 versus the nominal pipe size with minimal strainer port diameters of 1/4".

Foot valves shall be designed to be maintenance-free and suitable for installation in a vertical position only.

All components shall be of sturdy construction capable of withstanding repeated normal operation without failure or excessive wear.

Foot valves 2" thru 12" shall be rated for 200 psi and 14" and larger 150 psi.

The valve shall be equal in all respects to the Model 302BT as manufactured by the Flomatic Corporation.

Foot Valve Ordering Information

Quantity:

Type: 302BT

Size: Available 2" thru 24"

End Type: Flanged (ANSI class 125#)

Seat Ring: EPDM Standard or Buna-N optional

Patent # 6,024,121

Flomatic Corporation can accept no responsibility for possible errors in catalogues, brochures and other printed material. Flomatic Corporation reserves the right to alter its products without notices. This also applies to product already agreed. All trademarks in this material are property of the respective companies. All right reserved. ©2011 Flomatic Corporation. The drawings & information on this drawing sheet are the sole & exclusive property of Flomatic Corporation. Any reproduction, distribution, display or use of these drawings or information in whole or in part without written authorization of Flomatic Corporation is strictly prohibited.