FLOMATIC® VALVES
High Quality Valves Built to Last...®

15 Pruyns Island Drive
Glens Falls, NY 12801
Phone: 518-761-9797
Fax: 518-761-9798

CONTROL VALVE ORDERING AND QUOTATION FORM

PROJECT AND VALVE DETAIL INFORMATION

REQUIRED AT TIME OF ORDER

Customer:		ATTN:		Date:	
Address:		State:		Zip Code:	
Phone #:		Email:			
Purchase Order #:		Project Reference:			

REQUIRED SYSTEM INFO

Pipeline Size:	INCH	Media:		Temperature:	
Flow Rate Min:	GPM	Max:	GPM	Norm:	GPM
Valve Inlet Pressure (Static):		Valve Outlet Pressure (Static):			
Max Pump Pressure:	PSI	System TDH:			
Valve Orientation:	☐ Horizontal	☐ Vertical			

VALVE SPECIFICS

Connection Required:	☐ Flanged ANSI 150#	Body Style:	☐ Model 'C' - Full Port
	☐ Flanged ANSI 300#		☐ Model 'CF' - Reduced Port
	☐ FNPT		☐ Model 'CA' - Full Port Angle
Valve Trim:	☐ Stainless Steel (Standard)	Valve Coating:	☐ Standard Epoxy
	☐ Unleaded Bronze		☐ Double Epoxy
Pilot Piping:	☐ Copper (Standard)	Elastomers:	☐ Buna-N
	☐ Hard Pipe Stainless Steel (Optional)		☐ EPDM
	☐ Braided Stainless Steel Hose (Optional)		☐ Viton
	☐ Plastic		

Compliance/Certification:	☐ AIS	☐ BABA	☐ NSF 61	☐ Other _____

VALVE REQUIRED FUNCTION(S)

Model Requested:		Size:	INCH	
Series 100	Pressure Reducing Outlet Pressure Setting:	PSI		
Series 200	Altitude Valve Fill Height (From Centerline of Valve):	FT		
Series 300	Backpressure Sustaining Setting:	PSI		
Series 400	Pressure Relief Setting:	PSI		
Series 500	Nominal Operating Pressure:	PSI	Surge Relief Setting:	PSI
	Length of Discharge Pipe:	FT	Pipe Material:	
Series 600	Consult Factory			
Series 700	☐ Horizontal Float	☐ Vertical Float		
Series 800	Solenoid Voltage:	VOLTS	☐ AC	☐ DC
	When Solenoid is De-energized Should Main Valve Be:		☐ Open or	☐ Closed
Series 900	Maximum Rate of Flow Allowed:	GPM		
Model C1001	Maximum Rate of Flow Allowed:	GPM		

IF YOUR VALVE REQUIRES MULTIPLE FUNCTIONS PLEASE FILL IN ALL INFORMATION AS NEEDED

Other Comments or Remarks:	
Special Shipping Instructions:	

SUBMITTED AND SIGNED BY

PRINT NAME:	SIGNATURE:	DATE: