Danfoss Flomatic Corporation

15 Pruyn's Island Drive Glens Falls, NY 12801-4421 Tel: 800-833-2040 Direct Tel: (518) 761-9797 Direct Fax: (518) 761-9788 www.flomatic.com



NEWS RELEASE

FOR IMMEDIATE RELEASE



Contact: Dina Dieckert, Marketing Coordinator Telephone: 518-761-9797 ext 225 Fax: 518-761-9798

Fax: 518-761-9798 E-mail: dina@flomatic.com

Glens Falls, NY —Danfoss Flomatic Corporation introduces their new high flow direct acting pump control regulator valve, Model Cycle Gard® Hy-Flow Series C152EHF. This valve reduces rapid pump cycle with field adjustable by-pass and maintains a pre-set operating downstream pressure. The Hy-Flow features a low lead alloy body that has threaded female x female NPT connections with hex end OD and corrosion resistant internal components with a Nylon reinforced Buna-N diaphragm. The external adjustable by-pass allows for 1 to 5 GPM low flow tank fill rate to optimize the pump shut down run time. This valve can be installed vertical or horizontal and is ideal for flows up to 70 GPM.

For more information please call Danfoss Flomatic Corporation at 1-800-833-2040. You will also find detailed information on these products and all of their products at www.flomatic.com or please feel free to email them at flomatic.com