

Danfoss Flomatic Corporation

15 Pruyn's Island Drive
Glens Falls, NY 12801-4421
Tel: 800-833-2040
Direct Tel: (518) 761-9797
Direct Fax: (518) 761-9788
www.flomatic.com



Glens Falls, NY –Danfoss Flomatic Corporation introduces a new four-color bulletin covering their new additions to the growing Flo-Flex™ family of their rubber disc swing check valves. The model 745 provides the water and wastewater industry one of the broadest line of flexible rubber disc swing checks available on the market today. The flange to flange lay length is according to ANSI/AWWA C508-01.

The new Model 745BF features a back flush device used to manually operate the valve in the field. Common applications for this would be back flushing, system testing, priming of the pump, draining the lines and system testing. This valve option can be ordered at the time of purchase or installed in the field at any time. The other addition is their new Model 745PI which provides a valve disc position indicator that gives a distinct indication of the disc position during operation in the field. This swing check valve features a 45° seat with a steel/ductile iron valve reinforced rubber disc. The Ductile Iron 125# Flanged Body is Fusion Epoxy coated and can be used as pipe line cleanout and is based on a simple, proven and reliable construction. This valve has a disc stroke of 35° to minimize disc slam, low head losses, and a long rubber disc life. It can be installed in a horizontal or vertical orientation. This new bulletin explains the Model 745BFPI Flo-Flex™ Swing Check's features and benefits, dimensions and also suggested specifications.

For more information please call Danfoss Flomatic Corporation at 1-800-833-2040. You will also find detailed information on these products and all of their products at www.flomatic.com or please feel free to email them at flomatic@flomatic.com

Danfoss Flomatic
High Quality Valves Built to Last. . .